




850nm Diffractive Optical Element (DOE) Laser Module with 30,000-Random Dot Pattern, 67.7° x 53.4° FOV, 3V PCB Driver

MDOE850B200R303



Overview

The Lasermate MDOE850B200R303 laser module is an 850nm laser module integrated with 30,000-random dots pattern diffractive optical element (DOE). Designed for R&D purposes, the laser module comes with an adjustable focusing lens and with adjustable current to set the output power within a certain range.

Features

- 850nm diffractive optical element (DOE) laser module
- 30,000-random dot pattern
- Field of View (FOV): 67.7° x 53.4° (H x V)
- Low distortion and high uniform pattern
- Flexible package for R&D evaluation
- Distance tunable projection
- PWM drivable
- IEC 60825 eye safety standards

Applications

- Structured light for 3D sensing
- Machine vision

Specifications

Electrical-Optical Characteristics						
Parameter	Symbol	Min.	Typ.	Max	Unit	Conditions
Threshold current	I_{th}	-	18	30	mA	25 °C, $P_o=200mW$
Operating current	I_{op}	-	230	265	mA	25 °C, $P_o=200mW$
Operating voltage	V_{op}	-	2.1	2.3	V	25 °C, $P_o=200mW$
Slope efficiency	SE		0.95		mW/mA	$P_o=50-150mW$
Center wavelength	λ_c	840	850	860	nm	
Power input with PCB			3	3	V	25 °C, variable resistor included

Laser Diode Power Ratings					
Parameter	Symbol	Rating	Unit	Conditions	
CW output power (max)		350	mW		
Operating temperature	T_{op}	-10 to 60	°C		
Storage temperature	T_{stg}	-40 to 85	°C		

Mechanical Characteristics	
Diameter	8mm
Length	14~15mm
PCB driver	9(W) x 12(L) x 3(H)mm

Notes:


- Length varies as the position of the collimating lens varies case by case.
- Total module length varies with the length of metal pins left after welding.

Optical Specifications	
Total dots	30,000
Field of View (FOV)	67.7° x 53.4° (HxV)
Contrast ¹	≥ 3
Uniformity ² in FOV at 1m	$\geq 30\%$
Zero order ³	$\leq 0.2\%$

¹ Contrast: in the defined area, the ratio of the 95th percentile of the grayscale value over the mode grayscale value of the background, $C=I_{95\%}/I_{median}$


² Uniformity: the ratio of the grayscale value of the area at a given location to the grayscale value of the area in the center of the pattern, $U=I_{each\ area}/I_{max\ of\ each\ area}$

³ Zero order: (Power meter reading with DOE / Power meter reading without DOE) x 100%




Typical Characteristics

I-P Curve of Chip



Note: Module optical power output is lower.

Projection Pattern



Additional Notes

- Treat heat dissipation before setting the module to full power
- Avoid touching the emitting area or optical components of the module.
- Never look directly at the light from the emitting area.
- The laser modules are designated solely as OEM components for incorporation into the customer's end products. Therefore, it is the customer's responsibility to comply with the appropriate requirements of FDA 21CFR, section 1040.10 and 1040.11 for complete laser products. For the code of FDA regulations, please refer to [FDA Performance Standards for Light-Emitting Products](#) for detailed information.
- Specifications are subject to change without notice.



Lasermate Group, Inc.
 19608 Camino De Rosa
 Walnut, CA 91789 USA
 Tel: (909)718-0999
 Fax: (909)718-0998
sales@lasermate.com
www.lasermate.com