



LTC-T Series – TTL Modulated 635nm-980nm High Performance Laser Diode Modules

0.5in Diameter, Circular Beam, Adjustable Focus, APC Circuit



Overview

The Lasermate LTC-T series laser diode module system with TTL modulation is a self-contained laser diode system designed for OEM applications with adjustable focusing and APC circuit design features. The laser is designed as a high quality and high-performance laser diode module with flexible and adjustable characteristics for industrial heavy-duty users.

Features

- Wide range of wavelengths from 635nm to 980nm (including 650nm, 670nm, 780nm, 808nm, 850nm, 904nm)
- Wide range of output power up to 50mW
- High performance and low cost
- Adjustable focus
- Super fine pitch (0.25mm) for precision focusing
- Circular beam profile
- Singlet plastic collimating lens
- TTL modulation up to 100kHz

Product Overview

The following table shows the list of available part numbers, wavelength, optical output power, laser class, operating voltage, operating current, and operating temperature for LTC-T series laser modules.

Part Number	Wavelength (nm)	Optical output power (mW)	Operating Current typical (mA)	Operating & control voltage (V DC)	Laser class	Operating temperature (°C)
LTC6351A5-T	635	0.5-0.99	40	5	II	-10 to +50
LTC6352A5-T	635	1.2-2	40	5	IIIa	-10 to +50
LTC6354A5-T	635	2.5-4	55	5	IIIa	-10 to +50
LTC6501A5-T	650	0.5-0.99	30	5	II	-10 to +50
LTC6502A5-T	650	1.2-2	30	5	IIIa	-10 to +50
LTC6504A5-T	650	2.5-4	28	5	IIIa	-10 to +50
LTC6608A3-T	660	5-8	80	3.3	IIIb	-10 to +50
LTC6701A5-T	670	0.5-0.99	40	5	II	-10 to +50
LTC6702A5-T	670	1.2-2	40	5	IIIa	-10 to +50
LTC7802A5-T	780	1.2-2	30	5	IIIb	-10 to +50
LTC8082A5-T	808	1.2-2	30	5	IIIb	-10 to +40
LTC8502A5-T	850	1.2-2	30	5	IIIb	-10 to +50
LTC9042A5-T	904	1.2-2	30	5	IIIb	-10 to +50
LTC9044A5-T	904	2.5-4	40	5	IIIb	-10 to +50
LTC9804A5-T	980	2.5-4	45	5	IIIb	-10 to +40
LTC9808A3-T	980	5-8	60	3.3	IIIb	-10 to +40
LTC98014A3-T	980	10-14	70	3.3	IIIb	-10 to +40

Specifications of LTC-T Series Laser Diode Modules with TTL Modulation

Wavelength (nm)	635	650	670	780	808	850	904	980
Tolerance	+/-10 nm @ 25 °C							
Laser light	Visible Red				Infrared			
Laser class	Class II <1mW, Class IIIa <5mW, Class IIIb >5mW				Class IIIb			
Diode structure	Index guided							
Diode output power	5-50mW							
Operating current	30-90mA typical							
Operating voltage	5V DC (red wire "+" & black wire "-")							
Control voltage	Maximum 5VDC (yellow wire "+" & black wire "-")							
Drive circuit	APC with TTL modulation							
Modulation frequency	from DC to 100KHz							
Optics	Singlet plastic collimating lens							
Beam divergence	< 0.5 mrad							
Beam size @ 7 m	Dia. ~5 mm							
Beam profile	Circular							
Focus	Adjustable							
Operating temperature	-10 to +40 °C +50 °C, or +60 °C							
Connector	Black wire -, red wire + & yellow wire + signal							
Dimensions	Dia. 0.5" x L. 2"							
Weight	35 gm							
Option	Connecting to cross hair optics							

Additional Notes

- The LTC-T series laser modules are designated solely as OEM components for incorporation into the customer's end products. Therefore, it is the customer's responsibility to comply with the appropriate requirements of FDA 21CFR, section 1040.10 and 1040.11 for complete laser products. For the code of FDA regulations, please refer to [FDA Performance Standards for Light-Emitting Products](#) for detailed information.
- Additional heat sink may be needed if the laser module is operated continuously for a long period of time.
- Specifications are subject to change without notice.



Lasermate Group, Inc.
 19608 Camino De Rosa
 Walnut, CA 91789 USA
 Tel: (909)718-0999
 Fax: (909)718-0998
sales@lasermate.com
www.lasermate.com